



Dimensions: 105(D)x155.2(W)x110(H) mm

ADSK10-24H2

1000Watts, Three Phase power supply

Features

- High power density
- RoHS compliance
- Built-in cooling fan
- 3 year warranty
- Great reliability
- DIN Rail / Wall bracket mounting solution
- Over voltage protection
- Overload protection
- Over current protection
- Short circuit protection

Safety Standards



EN 55032 (Marking)

EMC Standards

EN55011	Class A
EN55022	Class A
EN55032	Class A
EN61000-4-2	Level 3
EN61000-4-3	Level 3
EN61000-4-4	Level 3
EN61000-4-5	Level 3
EN61000-4-6	Level 3
EN61000-4-8	Level 3
EN61000-4-11	Level 3

Model List

Model	O/P Voltage Adjustment	Min.	Loading Rated	Max.	Ripple Noise	Efficiency	Over Voltage Protection
ADSK10-24H2	+24VDC $\pm$ 10%	0A	40A	40A	350mVp-p	85%	27~30VDC

Specification

General

Switching Frequency		85kHz
Isolation Voltage	Input-Output	3000VAC /4242VDC
	Input-FG	1500VAC/2121VDC
	Output-FG	500VAC/ 710VDC
Isolation Resistance		100M Ω when Input-Output @500VDC
Operating Temperature		-40°C~40°C ambient
Derating		2.5% per degree from 40°C to 60°C

Website: <http://www.acro-powers.com/>
 E-mail: service@acro-powers.com.tw
 Tel: +886-2-22675015 Fax: +886-2-22674939

ACRO
ENGINEERING INC.

Specification

General

Storage Temperature	-40°C to +85°C
Relative Humidity	5%~95% RH, Non-condensing.
Temperature Coefficient	±0.04% of output voltage per °C
MTBF	60,000hrs Min. Per MIL-HDBK-217F, 25°C GB
Attitude During Operation	2000m
Installation position	Vertical
Vibration	Random Vibration, 10~500Hz. 3 axise

Input


Input Voltage	340-550VAC
Input Frequency	47~63Hz
Inrush Current(COLD START)	40A / 400VAC
Rated Input Current	4.0A Max. Vi=400VAC
Leakage Current	Input-output 0.4mA, Input-FG 5.5mA

Output

Output Voltage accuracy		±1%
Minimun Load		0%
Line Regulation		±1%, measuring from low line to high line rated load
Load Regulation		±2%, measuring from 20% to 100% of rated load at 380VAC input.
Voltage Trim Range		±10%
Rated Continuous Loading		40A@24VDC
Hold Up Time		20mS Min., Full load@400VAC.
Turn On Time		750mS
Rise Time		15mS
Fall Time		35mS
Transient Response	Recovery Time	2mS, Load change 50% to 100%
	Voltage Deviation	5%, Load change 50% to 100%
Efficiency		See model list, measuring at rated load and 230VAC input
Ripple and Noise		See model list, measuring by using a 0.1μF/630V metalize capacitor and a 47μF electrolytic capacitor parallel on the test point, at rated load and 230VAC input.

Specification**Protection**

Input Fuse	5A/250V x 3
Internal Surge Load Protection	Varistor, IEC6100-4-5
Degree of Protection	IP20
Short Circuit Protection	Autorecovery
Over Voltage Protection	Autorecovery
Rated Over Load Protection	110~130%
Overload protection	Power limited

Derating Curve**Mechanical Details**